Smart Diagnosis: Deep Learning Boosted Driver Inattention Detection and Abnormal Driving Prediction

Landu Jiang, Wen Xie, Dian Zhang*, Member, IEEE, Tao Gu, Senior Member, IEEE

Abstract-Inattentive driving is one of the high-risk factors that causes a large number of traffic accidents every year. In this paper, we aim to detect driver inattention leveraging on large-scale vehicle trajectory data while at the same time explore how do these inattentive events affect driver behaviors and what following reactions they may cause, especially for commercial vehicles. Specifically, the proposed system targets four most commonly occurring critical inattentive events including smoking, phone call, turning back and yawning. By applying a deep Convolutional Neural Network (Inception v3) with two data augmentation routines - Mixup and Smote, we are able to balance the training data distribution and improve the generalization of the classification model. Then based on the output derived from the inattention detection combining with Point of Interest and climate data, a Long Short Term Memory (LSTM) based model is deployed to predict driver upcoming abnormal operations on road (due to inattention) which may result in potential dangerous driving conditions such as sudden acceleration/deceleration, aggressive left/right lane change, etc. To evaluate our proposed system, we collect more than 120,000 real-world driving traces from over 200 drivers. The experimental results show that our model achieves a Weight Accuracy (WA) of 92.27% for inattentive driving detection and a Weight Accuracy (WA) of 91.67% for abnormal driving prediction, demonstrating its great potential of shaping good driving habits and promoting road safety.

Index Terms—Inattentive driving, deep learning, driver safety, large-scale data, data augmentation.

I. INTRODUCTION

Inattentive driving poses a major threat to road safety and has raised great interest in both academia and industry. Report in [1] shows that there were nearly 3000 fatal accidents every year in the United State from 2015 to 2019, and driver inattention accounted for 9% of all fatal accidents. Inattentive driving may lead to failure to notice traffic signs or yield traffic patterns, thus drivers may overreact when making turns or changing lanes. Especially for commercial vehicle drivers, due to the level of vehicle drivability and complex driving

(Corresponding author: Dian Zhang)

Tao Gu is with the Department of Computing, Macquarie University, Sydney NSW 2109, Australia (e-mail:tao.gu@mq.edu.au) conditions (e.g., frequent night driving), traffic accidents may occur more often than private vehicle drivers, causing serious loss of lives and property. Therefore, monitoring and understanding drivers' inattentive behaviors is essential to road safety measurement, shaping good driving habits and preventing road accidents.

To enhance driver safety, in-vehicle cameras have been widely deployed for monitoring driver's status in [2]-[4]. These vision based systems can accurately detect whether a driver is in an unsafe driving state (i.e., inattentiveness) by tracking facial states of the driver, but it will incur installation costs and the detection accuracy may be affected by lighting conditions (e.g., may not work well for night driving). You et al. [5] present a less expensive way to identify critical driving events (e.g., careless/aggressive lane changes or speeding, drowsiness/unfocused driving) by leveraging smartphone cameras and inertial sensors. However, the system may fail to capture objects if the phone is not properly placed in the vehicle [5]. In addition, we have seen great success in invehicle human activity recognition based on wireless sensing technologies such as Wi-Fi Channel State Information (CSI) and acoustic signals (e.g., ultrasound) [6]–[10]. Though these methods can achieve high recognition accuracy, they usually require extra infrastructures and time-consuming calibration to update the signal fingerprints. What's more, there have been a variety of driving safety systems that use smart sensors or wrist-worn devices. SMARTwheel [11] offers a safety product that has the linear potentiometers embedded in the steering wheel to determine whether a driver has their hands on or off the wheel. The wrist-worn devices like smartwatches have been applied to detect driver hand motion and dangerous invehicle activities [6]. The main disadvantage of such systems is that they still miss certain of unsafe events when the driving inattention has no hand motion involved.

On the other hand, driving trajectory analysis and vehicle dynamic measurement have been the fundamental tools that allow us to evaluate interactions between drivers, vehicles and road zones [12]–[14]. Though a number of approaches have used embedded sensors (e.g., accelerometer, gyroscope and GPS) on smart devices (e.g., smartphones) to track driving conditions [15], [16] as well as monitor driver smartphone use (e.g., calling, texting, and reading) to prevent distractions [17]–[19], other unsafe driving activities are not fully investigated. If a driver is or intend to be involved in any inattention or distraction, there could be a distinct change in vehicle movements (e.g., frequent steering-wheel correction activity) [20],

The first two authors contributed equally to this paper.

Landu Jiang is with the College of Computer Science and Software Engineering, Shenzhen University, Shenzhen 518060, China (e-mail: landu.jiang@mail.mcgill.ca)

Wen Xie is with the College of Computer Science and Software Engineering, Shenzhen University, Shenzhen 518060, China (e-mail: 1810273027@szu.edu.cn)

Dian Zhang is with the College of Computer Science and Software Engineering, Shenzhen University, Shenzhen 518060, China (email: serena.dian@gmail.com)

[21]. Such changes can be derived from the vehicle trajectory and thus be used as soft hints indicating inappropriate driving behaviors. More importantly, it is worth noting that in-vehicle inattentive activities are very likely to have an impact on driver following operations on road [22]. For example, when a driver is distracted due to smoking or phone call, he/she may not be able to react properly to the upcoming traffic alerts (e.g., sudden acceleration/hard braking, changing the lane aggressively), resulting in abnormal vehicle trajectory patterns. Predicting these unsafe driving conditions triggered by driver inattention in advance is desired, unfortunately, few work has been proposed addressing the issue.

Inspired by this, in this paper we present an inattentive driving analytics system to detect driver inattention while at the same time explore how these activities affect operations during driving, leveraging on large-scale vehicle trajectory data such as GPS trace, acceleration, speed, distance, and Point of Interest data. To achieve this goal, three modules are presented including unsafe events spotting, inattentive driving recognition and abnormal operation prediction. We first adopt Random Forest (RF) to spot the unsafe events and then apply a deep CNN model (Inception v3 with Mixup) to indentify driver inattentive behaviors. In addition, we use the Smote algorithm to augment the data and adopt the Mixup method to train the linear boundary avoiding model overfitting. Finally, a Long Short Term Memory (LSTM) based model is deployed to investigate the driver upcoming operations (affected by inattentive behaviors) and then predict dangerous driving events in advance (e.g., abnormal acceleration/deceleration, abnormal left/right lane change). Based on the vehicle trajectory data collected from long-term on-board diagnostics (OBD) devices, the proposed models can successfully identify four most commonly occurring inattentive driving events (e.g., smoking, phone call, turning back and yawning) and predict potential abnormal unsafe operations accordingly.

The main contributions of this paper are summarized as follows:

- 1) In this paper, we present an inattentive driving analytics system that leverages vehicle trajectory data to detect and study driver inattention, especially for commercial vehicles. The proposed system not only targets identifying in-vehicle inattentive driving activities but also focuses on predicting potential abnormal unsafe operations that may caused by driver inattention.
- 2) To detect and recognize inattentive driving conditions, we apply Inception v3 with the Mixup method to train a classifier model, not only solving the problem of discrete features and overfitting, but also distinguishing different types of driver inattentiveness. The Smote algorithm is also adopted to balance positive and negative samples and address the data sparsity.
- 3) To study the correlations between inattentive driving and abnormal operations, we leverage an LSTM based model by considering external features (i.e., the type of inattentiveness, Point of Interest and weather) to predict and avoid potential unsafe driving conditions in advance.
- 4) We conduct extensive experiments based on largescale commercial vehicle trajectory data. Our solution



Fig. 1. inattentive driving and abnormal driving conditions. (A), (B), (C) and (D) represents the smoking, phone call, turning back and yawn respectively. (E), (F), (G) and (H) represents abnormal acceleration, abnormal deceleration, abnormal lane change right and abnormal lane change left respectively.

outperforms other models which achieves a weighted accuracy at 92.27% for inattentive driving recognition and at 91.67% for abnormal operation prediction, which demonstrate that the proposed models are robust and effective.

To the best of our knowledge, our system is the first one that detects and recognizes driver inattentive behaviors by leveraging models based on large-scale trajectory data, while at the same time exploring the correlations between driving inattention and abnormal/unsafe driver behaviors to predict potential dangerous driving events (i.e., aggressive driving). It is worth noting that the proposed models are also capable of processing real-time data obtained from smart/on-board devices (e.g. smartphones) which have GPS and IMU sensors embedded. Therefore, this work has great potentials to assist driver in real driving condition and promote road safety.

The remainder of this paper is organized as follows. We describe the related work in Section II. We then introduce the design consideration in Section III, and present the system design in Section IV. We conduct our experiments in Section V, and then discuss the system latency and how can it be extended in Section VI. Finally, we conclude the paper and discuss the future work in Section VII.

II. RELATED WORK

Inattentive/aggressive driving detection basically can be classified into four categories: vision-based detection, wireless signal-based detection, wearable sensing-based detection and IMU-based detection.

Vision-based detection On-board cameras are widely used for real-time monitoring to determine whether the driver is distracted or fatigue [23]. However, it will incur additional costs and require specialized infrastructures in the vehicle. Meanwhile, smartphones are considered as an alternative option [24]-[26] to track driver's head position and eye directions. You et al. [5] used computer vision and

machine learning algorithms on the phone to detect driver inattention using the front-facing camera while at the same time tracking road conditions using the rear-facing camera. Ji et al. [23] proposed a non-intrusive vision-based prototype using remotely located cameras equipped with active Infrared Radiation (IR) illuminators to acquire video frames of the driver. Moreover, with the rise of deep learning, a number of systems leverage the Convolutional Neural Network (CNN) model to detection distraction driving [27]-[29]. Streiffer et al. [30] proposed a multi-modal analytics platform - DarNet, which could detect driver in-vehicle activities such as normal driving, talking, eating and reaching, etc. They employed a CNN model for video analysis collected from an inward facing camera and an RNN model for the data from mobile embedded sensors. Xing et al. [31] applied and evaluated three different pre-trained CNN models including AlexNet, GoogLeNet and ResNet50, focusing on seven common driving behaviors (e.g., secondary tasks). Despite the privacy issues, most vision-based approaches, however, are not always stable due to different setup conditions (e.g., weather, lighting and the device placement).

Wireless signal-based detection Many systems using wireless signals have been offered in driver behavior monitoring. Xie et al. [32] proposed a real-time drowsy driving detection system based on audio devices embedded in smartphones. It can detect nodding, yawning and abnormal steering of commercial vehicles in real time. Xu et al. [9] leveraged existing audio devices on smartphones to realize early recognition of inattentive driving events. Yang et al. [33] leveraged the existing infrastructure of car to detect driver phone use by estimating the range between the phone and car speakers. In addition, there has been active research work using Wi-Fi channel state information (CSI) for human motion sensing, WiCAR [8] employed a multi-adversarial domain adaptation network model to recognize various driver inattentive activities, while WiFind [10] applied Hilbert-Huang transform (HHT) based pattern extracting method to enhance driver fatigue detection. Although these methods achieved promising results, they are susceptible to the change of testing environments, such as environmental noise, changes in vehicle personnel, and window conditions.

Wearable sensing-based detection Inattentive driving detection using wrist-worn devices (e.g., smartwatch) emerges as a hot topic in recent years. Several systems have been offered to track driver hands position and analyze in-vehicle behaviors for preventing unsafe driving [34]. Bi et al. [35] presented SafeWatch, a system based on smartphone and smartwatches to estimate the posture of the driver's forearm and the positions of driver hands. SafeWatch could sense the motion of the vehicle and the driver's hands with two watches worn on both hands of the driver. Jiang et al. [6] focuses on driver's right hand motion to recognize secondary tasks and potential dangerous behaviors. But it only tracks one single hand movements and the basic assumption is the movement always starts at the steering wheel. Moreover, Lee et al. [36] also proposed a standalone system that detects driver drowsiness using smartwatch only. The system is able to determine the drowsiness level based on different types of driver behaviors computed from the motion data. Thus it is no doubt that wearable sensing if capable of detecting unsafe driving activities. However, drivers still need to wear the device on their hands, and one single smart device can not capture all types of unsafe events.

IMU-based detection A number of IMU-based systems using sensors on cars/smartphones have been proposed for unsafe/inattentive driving detection. Wang et al. [37] used embedded sensors in smartphones (i.e., accelerometers and gyroscopes) capturing the differences of centripetal acceleration readings during turns. Based on the information, it can estimate the position of the smartphone in the vehicle - at driver side or passenger side, thus prevent the phone calling/texting if there is a high chance that the driver is holding the device. Johnson et al. [38] also proposed a method for the localisation of a smartphone inside a vehicle using the motion data acquired from user's phone. In addition, Chen et al. [39] provided a smartphone-based system for fine-grained abnormal driving behavior recognition. By leveraging the Support Vector Machine (SVM), it is able to distinguish six different driving patterns accurately. Bhaskar et al. [40] presented EyeAwake, a drowsy driving detection system that employs a set of sensors including IR detector, accelerometer, thermistor and phototransistor. EyeAwake detects driver drowsiness by checking human behavioral and physiological characteristics such as eye blinking rate, unnatural head nodding/swaying, breathing rate and heart rate. Towards the most related work in detecting driver distraction, Ahmed et al. [18] developed a simulation platform - CAREN to study the impact of smartphone use on driver operations. The testing data from smartphone sensors (i.e., accelerometer and gyroscope) shows that when a driver is holding the phone and attempting to text, call or read the massage, the signal patterns will have subtle changes that are distinct from normal/safe driving states [41].

Though above approaches well examined the capability of different smart sensing techniques as well as IMU-based platforms, only a few specific inattentive activities (i.e., smartphone use related events) have been addressed. Different from existing approaches, in this paper we leverage trajectory data to identify a number of driver distractions that most commonly occurred in the vehicle. In addition, we further explore the driver reaction caused by such inattentive activities, thus the proposed model is able to predict the upcoming abnormal behaviors in advance and has great potential to reduce the risk of traffic accidents.

III. DESIGN CONSIDERATION

A. Background and Motivation

As the incidence of traffic accidents increases year by year, safe driving has become one of the most concerned topics of intelligent transportation systems. It is desirable to study and analyze unsafe driving behaviors, especially for commercial vehicles which are more likely to cause fatal accidents since it needs a longer breaking distance to fully stop them due to the large momentum and inertia [42]. Generally, drivers that operate commercial vehicles may experience more complex driving conditions than passenger cars which may cause distractions such as receiving more phone calls/orders or taking care of passengers [43]. In addition, they may also become fatigue after long-distance driving or working at midnight. An efficient behavior analysis system could help commercial vehicle drivers to raise risk awareness and shape good driving habits to avoid accident.

Moving along this direction, in this paper we leverage largescale trajectory data to study unsafe driving events especially for commercial vehicle drivers. Unlike existing driver alert systems [18], [37], our approach does not only focus on detecting inattentive activities, but also aims to predict potential dangerous driving conditions in advance. Once drivers' unsafe behaviors are identified, there will be a high chance that an accident may occur in a few seconds. Thus predicting such dangerous conditions is important and necessary, which can prompt the vehicle safety systems (e.g., Electronic Stability Control, Intelligent Speed Adaptation, Collision Avoidance System) to better react to incoming operations accordingly and avoid traffic accidents. For example, when the driver is inattentive (e.g., on the phone) and suddenly notice that there are people crossing the road ahead, the driver may behave aggressively to avoid collision while the system should be able to automatically adjusts the torsion force of the steering wheel and prepare for hard braking.

B. Challenges

Analyzing driver behaviors leveraging large-scale trajectory data is very challenging. Firstly, the total number of inattentive events in one single path is limited and each path may contain different types of driving inattention events. Thus the density of the target samples (i.e., inattentive driving) in the dataset is sparse and the amount of data in each class is not equally distributed - imbalanced. The existence of unsafe trajectories only accounts for 48% of the entire trajectory collection, and the average number of points with GPS alerts (for unsafe driving) is less than 8% of each unsafe trajectory. Because the driver preforms normally (safely) most of the time while the unsafe driving events only occur accidentally. Secondly, due to the huge amount of trajectory data, there are missing GPS points on certain trajectories and many GPS points are not correctly aligned on the path. Thirdly, other factors on road may also affect the performance of driving and result in different dangerous driving conditions especially when the driver is inattentive (as discussed in Section V-E). In order to handle such issues and build a robust model, data augmentation and interpolation schemes are required. In addition, the proposed system should also take the external data such as Point of Interests (POIs) into account for driver operation/reaction prediction after an inattentive driving event is identified.

C. Inattentive Driving and Abnormal Driving Conditions Scenarios

In this paper, we aim to propose an inattentive driving analytics system to detect driving inattentive and warn the driver of abnormal driving in the inattentive driving in advance. Specially, we not only detect whether the driver is inattentive while driving, but also combine the driver's



Fig. 2. The distribution of the number of inattentive trajectories in the city in August 2018.

inattentive behavior and POI, weather to further predict the driver's abnormal driving condition. We tested four common inattentive behaviors: smoking, phone call, turning back, and yawning, as illustrated in Figure 1. The abnormal driving conditions are abnormal acceleration/deceleration, abnormal lane change left/right.

Smoking (A): Smoking is a common in-vehicle activity for drivers who are addicted to smoking. Because there are some drivers who think that smoking can relieve driving fatigue, but in fact this produces hallucinations.

Phone call (B): Commercial vehicle drivers use mobile phones more frequently than private cars. According to a survey, 86.3% of drivers believe that reading text messages and smoking on their mobile phones will filter out the troubles of long-distance driving. Due to the danger of using mobile phones while driving, both the United States and Canada prohibit the use of mobile phones while driving [44].

Tuning back (C): When the commercial vehicle reaches the destination or a certain POI area, the driver's eyes will turn to the road signs or landmark buildings outside the vehicle to identify the direction of the destination.

Yawning (D): Yawning is the most common in-vehicle activity for drivers. As commercial vehicles require longer driving time, drivers are more prone to fatigue.

Abnormal acceleration/deceleration (E and F): After the driver's inattentive behavior, it will affect the normal control and judgment. According to the report [1], if a vehicle is moving forward at a speed of 60km/h and suddenly decelerates, under the action of inertia, the distance that the vehicle slides forward is proportional to the mass, and the resulting loss is huge.

Abnormal lane change left/right (G and H): Changing lanes in normal driving may not have adverse effects. However, the left and right lane changes caused by slamming the steering wheel after an inattentive behavior are prone to the danger of rollover, leading to traffic accidents.



Fig. 3. System Overview. Inattention type includes smoking, phonecall, turning back and yawning. Abnormal operation includes sudden acceleration/deceleration, aggressive left/right lane change.

It is worth noting that inattentive driving behaviors are all unintentional behaviors under the driver's ideology, while aggressive driving is some abnormal operations caused by the driver's stimulation of certain distracted behaviors.

IV. SYSTEM DESIGN

In this section, we give a detailed discussion of the system architecture and algorithms for inattentive driving analysis.

A. System Overview

The proposed system mainly includes three components: 1) Data Pre-processing; 2) Unsafe Event Spotting; 3) Inattentive Driving Recognition; 4) Abnormal Operation Prediction. As illustrated in Figure 3.

The trajectory data in the real road driving environments may contain ambiguity, uncertainty and noise, and only a limited number of driving cycles contain the target events (i.e., unsafe driving). To address these issues, we firstly employ data segmentation and augmentation to format and enrich the original dataset. We then proceed the event spotting module to obtain interval candidates from the entire trajectory and filters out the input if it does not belong to the task domain. When a target period of inattentiveness is spotted/detected, the classification module leveraging Deep CNN model - Inception v3 with Mixup method will be triggered to recognize the exact type of driver inattention. Once the type of an inattentive driving event is identified, the system is able to predict the driver upcoming reactions by using a well-trained LSTM based model while at the same time considering the external features (e.g., POI and weather), thereby reducing the risk of potential dangerous driving conditions.

B. Data Pre-processing

1) Data Segmentation: In order to capture the target events, we employs a sliding window with a fixed length m (a time



Fig. 4. Data Pre-processing: (A) is the trajectory classification stage, which mainly divides the trajectory into time windows with the same length, and then extracts the basic features of each time windows, including acceleration \mathcal{A}_k , distance \mathcal{D}_k , speed \mathcal{S}_k , altitude difference \mathcal{C}_k , POI \mathcal{P}_k , weather \mathcal{W}_k and peak period \mathcal{R}_k . (B) is mainly to extract the speed offset x_{offset} and y_{offset} between two GPS points in the abnormal time windows. The red box represents the distribution of GPS points on the trajectory when the vehicle is driving in an area (like a commercial area).

window contains m GPS cells) along with each trajectory for feature extraction as shown in Figure 4. The length of the window buffer m is set as 6 which has been proved to be effective in the test and the detection latency is discussed in SectionVI-A. In one time window, each GPS cell contains latitude, longitude and altitude. The definition of the j-th GPS cell GPS^j is:

$$GPS^{j} = \left[lat^{j}, lon^{j}, alt^{j} \right]$$
(1)

Therefore, the k-th time window of the trajectory can be expressed as a vector tr_k , which contains a group of latitude, longitude and altitude from GPS cells,

$$tr_{k} = \left[GPS_{k}^{1}, GPS_{k}^{j}, ..., GPS_{k}^{m}\right] \left(1 \leq j \leq m\right), \quad (2)$$

then one driving path can be presented as T:

$$\mathcal{T} = [tr_1, tr_2, \dots, tr_k, \dots tr_n] \left(1 \le k \le n \right), \tag{3}$$

where n represents the total number of time window from one single driving path. The stride between time windows is one GPS cell (2 seconds), and each selected time window (interval) will be used as the input that fed into modules at next step.

2) Data Augmentation: The traditional data augmentation solution is to replicate the minority samples repeatedly, with the same number of samples in different categories. But such method can also cause overfitting of the training model. In our design, the Synthetic Minority Oversampling Technique (Smote) [45] is used to over-sample the elements in the dataset \mathcal{T} that reaches a balanced distribution, the basic steps of Smote algorithm are as follows:

(1) Take a random sample from the minority class tr_p in the set \mathcal{T} , and use the Euclidean distance to calculate the distance from this sample tr_p to all samples in the set. Then select κ nearest neighbor samples of this type, that is, κ with smaller Euclidean distance;

(2) Set a sampling ratio according to the unbalanced ratio of the sample to determine the sampling magnification β . Then, randomly select one sample among the κ neighbors of this type of sample tr_p , assuming that the selected nearest neighbor is tr_p as the basis for subsequent calculations;

(3) For $\widehat{tr_p}$ selected in (2), construct a new sample tr_{p_new} with the original sample according to formula,

$$tr_{p_new} = tr_p + rand(0,1) \times \left(\widehat{tr_p} - tr_p\right), \qquad (4)$$

so, the augmentation collection of samples of the smote algorithm.

$$\widehat{\mathcal{T}} = Smote(\mathcal{T}),\tag{5}$$

In the Smote algorithm, the ratio parameter is used to set the number of positive and negative samples so that the ratio reaches 1:1.

C. Event Spotting

1) Feature Extraction: At this stage, the basic features of are derived from each time window, including average acceleration \mathcal{A} , average distance \mathcal{D} , average speed \mathcal{S} , altitude difference \mathcal{C} . In addition, as shown in Figure 2, the occurrence of inattentive event is highly related to the specific time periods of the day such as the early morning period or the midnight period. Thus we add the time period \mathcal{R} as an additional feature in driving inattention detection. Therefore, the feature vector of the k-th time windows tr_k^s can be formulated as $tr_k^s = [\mathcal{A}_k, \mathcal{D}_k, \mathcal{S}_k, \mathcal{C}_k, \mathcal{R}_k]$. Then the input data set of the model can be defined as $\widetilde{\mathcal{T}^s} = [tr_1^s, tr_2^s, ..., tr_k^s, ..., tr_n^s]$, where n represents the number of time windows.

2) Driving Event Spotting: As discussed in section III-B, only a limited number of time periods in the entire trajectory may be involved in unsafe driving. To distinguish the target interval, we use Random Forest (RF) [46] algorithm to make a binary decision based on the input data $\tilde{\mathcal{T}}^s$. There are two types of labels for the input data, namely alarm and normal. Alarm refers to the unsafe driving pattern detected and normal means no target events found during this time period. Applying RF based event spotting not only allows us to filter out non-related data and increase the training speed (RF outperforms other method as shown in Figure 7), but also enable the system maintain the minimum functionality to alert drivers when other components (i.e., inattention recognition and abnormal operation prediction) can not work properly.

The main steps of RF model used in event spotting include: First, there are N samples randomly selected with replacement in the sample set $\tilde{\mathcal{T}}^s$. These N samples are used to train a decision tree as the samples at the root node of the decision tree. Each sample has 5 attributes, and h out of these five attributes are selected (h << 5). Then, from the h attributes, information gain is used to select one attribute as the split attribute of the node. Finally, in the process of forming the decision tree, each node is split according to the previous step. Until it can't be divided. Eventually constitute a RF model.

D. Inattentive Driving Recognition

This module consists of two phases: feature formulation and event recognition. The recognition model proposed in this paper is a deep Convolutional Neural Network (CNN), which is composed of Inception v3 [47] and Mixup method [48].

1) Feature Formulation: At this stage, firstly, we set the previous GPS cell GPS^{j-1} before the *j*-th GPS cell as a reference point, and calculate $GPS^{j}(1 \leq j \leq m)$ and GPS^{j-1} velocity offset along the x-axis and y-axis. Assuming that the angle between GPS^{j} and GPS^{j-1} is α , the velocity offset along the x and y axis is defined as:

$$\nu_{k_x}^j = \nu_k^j \times \cos\alpha, \tag{6}$$

$$\nu_{k_{y}}^{j} = \nu_{k}^{j} \times \sin \alpha, \tag{7}$$

where ν_k^j represents the Instantaneous velocity of the vehicle when it reaches the *j*-th position.

This three vectors ν_k^j , $\nu_{k_x}^j$, $\nu_{k_y}^j$ $(1 \le j \le m)$ of the k-th time windows form a three-dimensional vector. The vector of the k-th time windows tr_k^o is defined as:

$$tr_{k}^{o} = \begin{pmatrix} \nu_{k}^{1}, \nu_{k}^{2}, \dots, \nu_{k}^{j}, \dots, \nu_{k}^{m} \\ \nu_{k_{x}}^{1}, \nu_{k_{x}}^{2}, \dots, \nu_{k_{x}}^{j}, \dots, \nu_{k_{x}}^{m} \\ \nu_{k_{y}}^{1}, \nu_{k_{y}}^{2}, \dots, \nu_{k_{y}}^{j}, \dots, \nu_{k_{y}}^{m} \end{pmatrix}, \quad (8)$$

so, one driving path can be formed as $\widetilde{\mathcal{T}^o}$:

$$\widetilde{\mathcal{T}^o} = [tr_1^o, tr_2^o, ..., tr_k^o, ..., tr_n^o] (1 \le k \le n),$$
(9)

where n represents the number of time windows in one single driving path.

2) Inception v3: Inception v3 is designed to solve the difference in the proportion of the prominent part of the image [49]. It learns the image data set by setting multiple convolution kernels at the same time, and has a good fit. It is worth noting that in the time windows set, the distribution of alarm points for each time windows is also very sparse. This cause the choice of convolution kernel to be more biased. If the CNN is simply used, overfitting will occur and it will be difficult to transmit the gradient update to the entire network. Inception v3 adds Batch Normalization (BN) [50] to each batch of data on the basis of Inception, which can reduce the dependency on parameter initialization, thereby improving the training speed and preventing network saturation. The BN is define as:

$$\widehat{b^{(s)}} = \frac{b^{(s)} - E[b^{(s)}]}{\sqrt{Var(b^{(s)})}},$$
(10)

where $E[b^{(s)}]$ refers to the average value of neuron in the *s*-th batch of data; $Var(b^{(s)})$ refers to the standard deviation of the input value of each neuron in the *s*-th batch of training data.

The dataset \mathcal{O} is used to train. The dimension of each vector o is $3 \times 1 \times m$. Therefore, we change the three initial convolution kernels of Inception v3 and set them to 1×1 , 1×1 , and 1×1 respectively. The structure is shown in Figure 5. Adding the 1×1 convolutional layer in front of the 1×3 , 3×1 two convolution kernels will help limit the number of channels and improve computing power. After the Inception v3 network, the convolution results of four different convolution kernels can be obtained, then filter concatenate them to the next network.

3) Mixup: To improve the generalization ability of the model and reduce over-fitting. We use the Mixup method to expand the virtual samples between different categories. We first choose two different types of samples and labels $(batch_{tr_i^o}, batch_{L_i})$ and $(batch_{tr_j^o}, batch_{L_j})$ then generate mixed samples and labels $(mixbat_{tr^o}, batch_L)$.

$$mixbat_{tr^{o}} = \lambda \times batch_{tr^{o}_{i}} + (1 - \lambda) \times batch_{tr^{o}_{j}},$$

$$mixbat_{L} = \lambda \times batch_{L_{i}} + (1 - \lambda) \times batch_{L_{i}},$$

(11)

where λ represents the mixing coefficient, λ - Beta(α, α), $\alpha \epsilon(0, \infty)$, α controls the intensity of interpolation between the feature-target vector.

Since minimizing the average error of training data is the purpose of neural networks. Such learning rule is also called the principle of Empirical Risk Minimization (ERM) [51]. However, because the driving habits of each driver are different, it leads to the appearance of adversarial samples (that is, the test distribution is slightly different from the training sample data). The traditional ERM method has less ability on interpretation and generalization in this case. Therefore, the



Fig. 5. Inception v3 with Mixup Model.

data enhancement method Mixup [48] proposes Vicinal Risk Minimization (VRM) by expanding the data of the same type in the dataset.

$$\mu\left(mixbat_{tr^{o}}, mixbat_{L}|batch_{tr^{o}_{i}}, batch_{tr^{o}_{j}}\right) = \frac{1}{n} \sum_{j}^{n} E\left[\delta\left(mixbat_{tr^{o}}, mixbat_{L}\right)\right],$$
(12)

where $mixbat_{tr^o}$, $mixbat_L$ represents the samples and label enhanced by Mixup. $batch_{tr_i^o}$ and $batch_{tr_j^o}$ represents the source sample and label respectively. When $\alpha \rightarrow 0$, it returns to the ERM.

E. Abnormal Driving Prediction

At this stage, we predict the abnormal driving operation by leveraging the information derived from inattention event recognition combined with the external data.

1) Feature Combination: To formulate the input vector of the prediction model, 5 basic features are considered at each GPS point. The feature vector of the j-th GPS point in the time window k can be expressed as:

$$GPS_k^j = \left[\nu_k^j, \mathcal{N}_k^j, \mathcal{P}_k^j, \mathcal{W}_k^j, \mathcal{L}_k\right], \qquad (13)$$

where ν_k^j , and \mathcal{N}_k^j represent the velocity and the heading angle change of the vehicle. In addition, the external factors \mathcal{P}_k^j (POI) and meteorological \mathcal{W}_k^j are taking into account as the existence of contextual data (the data can be obtained



from public websites such as google map and weather underground ¹), and \mathcal{L}_k represents the label which is the type of inattentive detection in the *k*-th time window.

2) LSTM Based Prediction: As illustrated in Figure 6, we are able to formulate the vector tr_k^p (one time window) using GPS_k^j as the input to the LSTM model, and each input vector tr_j^p has a specified size of 5 (the length of time window m = 5). Moreover, we collect the event at the next GPS point (2 seconds later) as the ground truth, and define the label as \mathcal{D}^{k+1} (normal or abnormal). Then the vector of all GPS points of the time window k is:

$$tr_k^p = \left[GPS_k^1, GPS_k^2, ..., GPS_k^j, ..., GPS_k^m\right], \qquad (14)$$

and the dataset of input vectors is define as:

$$\widetilde{\mathcal{T}}^p = \left[tr_1^p, ..., tr_k^p, ..., tr_n^p\right],\tag{15}$$

Then we use the data from $\widetilde{\mathcal{T}}^p$ for LSTM model training, and finally get the prediction of abnormal operation type.

According to the input vector tr_k^p , we initialize the model with 5 LSTM cells, and the last element h^m is selected as the output to the softmax layer. At the final step (the classification layer), five classes are specified (i.e., normal driving, abnormal acceleration, abnormal deceleration, abnormal left lane change and abnormal right lane change) by passing through a fully connected layer.

V. EVALUATION

In this section, we conduct extensive experiments to evaluate algorithms and models that proposed in this paper for inattentive driving analytics. We first present the experiment setup and datasets, and then introduce the baselines used for comparisons of each module. Moreover, we summarize the results of unsafe event spotting, inattentive driving recognition and abnormal driving prediction, a detailed discussion is also provided.

Fig. 7. The Accuracy, Precision, Recall and F1-Score between Random Forest and other Machine Learning Algorithms.

A. Experiment Setup

We conduct experiments using a large-scale vehicle trajectory dataset provided by the commercial insurance company. The company installed OBD-II devices and cameras on the insured vehicles to record driving dynamics and critical events. The time period of data collection is one year - from September 1, 2017 to September 30, 2018. The dataset contains over 120,000 driving trajectories captured from nearly two hundred vehicles. In the training phase, we are able to derive more than 100,000 driving trajectory vectors to for unsafe event spotting, inattentive driving recognition and abnormal operation prediction. We implement our deep model using PyTorch which is a high-level neural network framework based on the Torch library. The model training phase was done using a server with NVIDIA GeForce GTX 1080 Ti GPU and 64GB CPU memory. For the optimization method, we use a momentum of 0.9 and a basic learning rate of 0.01. In addition, we set the parameters of LSTM model epoch=500, batch=128, and the optimizer chooses Adam.

B. Baseline and Metrics

We evaluate the performance of each module in our proposed system (i.e., unsafe events spotting, inattentiveness detection and dangerous event prediction) by using different baselines as follows:

- Unsafe Event Spotting: In this module, we test a number of popular machine learning algorithms that are widely used for classification and regression, such as GBDT (Gradient Boost Decision Tree) [52], Support Vector Machine (SVM) [53], K-Nearest Neighbor (KNN) [54] and Linear Regression (LR) [55].
- **Inattentive driving Recognition**: We compare the proposed method (Inception v3) with the classic version of CNN model.
- Abnormal Driving Prediction: In this module, we use D^3 system [39] as the baseline, which is an SVM-based model that can train the features and output a classifier to perform the fine-grained identification.



Fig. 8. The Classification Matrix of with or without Mixup.

 TABLE I

 RUNNING TIME OF EACH MODEL FOR EVENT SPOTTING

	Models				
	GBDT	KNN	SVM	LR	RF
ET (s)	12.074	0.016	0.632	0.003	0.028

In addition, we use accuracy, precision, recall and f1 scores to evaluate methods for unsafe event spotting (i.e., RF, GBDT, SVM, KNN and LR). For multi-class classification - inattentive driving recognition and abnormal driving prediction, weighted average of accuracy (WA), precision (WP), recall (WR) and f1 scores (WF) are applied:

$$WA = \sum_{i=1}^{N} \frac{TP_i + FN_i}{\sum_{j=1}^{N} TP_j + FN_j} \times accuracy_i,$$

$$WP = \frac{\sum_{i=1}^{N} TP_i}{\sum_{j=1}^{N} TP_j + FP_j},$$

$$WR = \frac{\sum_{i=1}^{N} TP_i}{\sum_{j=1}^{N} TP_j + FN_j}, WF = \frac{2 \times WP \times WR}{WP \times WR}.$$
(16)

where WP is the sum of true positives across all classes divided by the sum of true positives and false positives across all classes, while WR is the sum of true positives across all classes divided by the sum of true positives and false negatives across all classes. Then we can calculate the WA and WFaccordingly. What's more, the confusion matrix and histogram are also used in the evaluation to present the classification results.

C. Unsafe Event Spotting

As shown in Figure 7, the RF model outperformed other machine learning algorithms that reached accuracy, precision, recall and f1-score at 90.92%, 92.25%, 91.76% and 91.00%, respectively. As we use Smote algorithm to balance the data sets, we are able to train a more generalized model by artificially synthesizing and adding new samples that benefits



not only unsafe event spotting but also inattentive driving recognition. As a result, the digital ratio between the training sample, the verification sample and the test sample is 8:1:1. For other models (GBDT, SVM, KNN, LR), we conducted experiments according to the settings in the original or highly related paper.

The Random Forest is an ensemble model of decision trees. Time complexity for building a random forest is $O(u * v * n \log(n))$, where u is the number of decision trees (10 in our design), n is the number of records for training and v is the number of attributes in the input data. While the computational complexity at test time for a random forest is O(u*D), where D is the maximum depth of the trees (no greater than 5 in our cases). In addition, we also measure the average execution time (ET) of RF and other models for one single input as shown in Table I. The RF model could perform an accurate and timely detection on unsafe driving events.

D. Inattentive Driving Recognition

In this section, we will evaluate our module Inception v3 with Mixup and compare it with other baselines based on the dataset $\widehat{\mathcal{T}^o}$ discussed in Section IV-D1. The dataset $\widehat{\mathcal{T}^o}$ contains more than 6000 samples, among which the ratio of smoking, phone call, turning back and yawn is 2:3:2:3. The ratio of training samples, test samples and validation samples is 8:1:1. We can see from the Table II, our proposed model - Inception v3 with Mixup outperforms other methods.

Comparing to the classic machine learning methods (i.e., SVM, GBDT) and deep learning methods (i.e., CNN, Inception v3). We can observe that the Inception v3 with Mixup could achieve much better performance by considering the locality of the prominent features. In detail, taking the input dataset $\widehat{\mathcal{T}^o}$ as an example (shown in Table II), the WA of Inception v3 with Mixup is relatively 17.37% higher than SVM, 21.36% higher than GBDT, 11.73% higher than DNN, and 12.83% higher than CNN. The main reason is that our model does not only expand the breadth of the network, focusing on the extraction of feature locality, but also deepen the depth of the network.

Model	$\mid \mathcal{T}^{o}$					
Woder	WA (%)	WP (%)	WR (%)	WF (%)	ET(s)	
SVM	76.24	75.26	76.35	76.35	0.946	
GBDT	82.56	71.23	72.10	72.31	0.795	
DNN	81.45	82.25	81.02	81.45	0.778	
CNN	80.43	79.76	80.70	79.79	0.298	
Inception v3	89.13	88.86	89.05	88.69	0.371	
Inception v3 with Mixup	92.27	92.30	92.27	92.27	0.384	

 TABLE III

 The parameters of the proposed CNN model.

Туре	Input size	Output size
conv 1	36x1x3	18x1x8
conv 2	18x1x8	18x1x64
Inception b1	18x1x64	9x1x64
Inception b2	9x1x64	9x1x128
Inception b3	9x1x128	5x1x128
Fully-connected	5x1x128	5x1x256

TABLE IV Abnormal Driving Prediction Performance

Model	<i>Τ</i> ^o WA (%)	WP (%)	WP (%)	WF (%)	ET (s)
SVM	86.17	86.36	86.36	86.36	0.523
RNN	90.24	90.07	90.07	90.07	0.296
LSTM	91.67	90.18	90.18	90.18	0.312

Moreover, we choose a simplified Inception v3 structure

since it mainly focuses on saving computational power while

maintaining the accuracy by modifying the previous Inception

Networks. The number of parameters/size of each layer in

Inception v3 model is illustrated in Table III, and the detail

of each Inception block is shown in Figure 5. The average

execution time (ET) of different models for a single event

is presented in Table II. Though the time is longer than a

standard CNN model, it is acceptable (still less than half a

With/Without the Mixup: In order to further understand

second) considering the recognition accuracy.

Fig. 9. The weighted average of accuracy (WA), precision (WP), recall (WR) and f1 scores (WF) of abnormal driving condition prediction.



the effectiveness of Mixup method in the deep learning model, we use model ablation to explore its functionality. It is worth noting that the initial convolution kernels of Inception v3 are 1×1 , 1×1 , and 1×1 respectively. With these parameters unchanged, the performance of the model without Mixup was tested. As shown in the Table II, we can see that the model performance became 3.40% higher with Mixup. This is because Mixup reduces the sensitivity of adversarial samples. As shown in sub Figure 8(a) and 8(b), it indicates the results of the category detection with or without Mixup. We can see that the classification detection combined with Mixup can better distinguish the categories of smoking and yawn. This is because Mixup performs data expansion on training set samples, that is, performs linear modeling on different types of samples to enhance the linear expression between training samples. In addition, Mixup improves the robustness of adversarial samples, especially on large-scale datasets.

Fig. 10. The distribution of abnormal operations caused by each type of inattentive driving.

E. Abnormal Driving Prediction

Table IV shows the prediction results of our proposed **LSTM** based model comparing with the baseline Recurrent Neural Network [56] (RNN) and SVM. The vector $\widehat{\mathcal{T}}^p$ is used as input to LSTM module. We can see that, our LSTM has the best performance among the other models. The details are as follows. LSTM outperforms RNN, SVM by 1.56%, 6.00% respectively. The reason why our LSTM based model is better than RNN is that it considers filtering of the past state in the





(a) In the four parts of the truck's trajectory, the driver has abnormal driving behaviors due to inattentive driving.



(b) In the four parts of the bus's trajectory, the driver has abnormal driving behaviors due to inattentive driving.

Fig. 11. The figure shows the trajectory of the truck (a) and the bus (b).

time series, so as to select the state which has more effects on the current state, instead of simply using the most recent state.

To better understand the computational complexity of our model, we summarize the number of parameters in the LSTM network. There are 4 neural network layers including 3 gates - read/input, write/output, forget, as well as one cell state. Thus, the total number should be $4 * (n * (m + 1) + n^2)$ based on the structure of LSTM. The average execution time (ET) for abnormal driving prediction is shown in Table IV. We can see that the proposed model achieved a higher accuracy with just a few extra milliseconds.

With/Without External Features: In order to understand the effects of additional features (POI) on event prediction. The results show in Table V. The WA with/without external features are 91.67 and 89.23 respectively. This is because when the vehicle is driving to the POI area, the driver needs to observe the places on both sides of the road during driving, which leads to some inattentive driving behaviors. These inattentive behavior may cause the driver to perform dangerous driving operations.

In order to take a further look into the details, the prediction results for each type of abnormal driving are shown in Figure 9, and all of them are over 92%. Moreover, we also investigate how different types of inattentive events affects the driver behaviors. As shown in Figure 10. Statistics represent the number of test sets, and predictions represent the correct number of predictions. The number of abnormal left lane changes due to the distracted behavior of the driver's smoking was 993, accounting for 58.31%. The number of abnormal right lane changes due to phone call is 1018, accounting for 63.94%. The number of abnormal deceleration operations due to the turning back is 1124, accounting for 67.06%. Due to the phone call, the number of abnormal left lane changes by the driver was 934, accounting for 58.48%... More importantly, by comparing the ground truth of abnormal event distribution

 TABLE V

 The metrics of with/without external feature.

	$ \widetilde{\mathcal{T}^o}$			
	WA (%)	WP (%)	WP (%)	WF (%)
without POI	89.23	89.35	89.35	89.35
with POI	91.67	90.18	90.18	90.18

with our prediction results in Figure 10, it demonstrates that our proposed model can accurately infer the potential unsafe operations in advance based on driver current inattentive states.

We also study and analyze the correlations between inattentive driving and abnormal behaviors using real driving cases. Figure 11(a) shows a trajectory sample of a truck from 1:45 to 3:13 in the morning and the destination is a construction area (i.e., warehouse, factory). The drivers always need to contact/call other people to arrange the deliver time or find the gate to enter, etc. Generally, the driver may use the right hand to hold the smartphone and only the left hand is on the steering wheel. Thus the driver will do left turn more frequently due to human nature to avoid obstacle on road which results in abnormal left lane changes. Figure 11(b) shows a trajectory sample of the van from 17:56 to 18:50 in the afternoon, and the vehicle traveled through a residential or commercial POI. The driver may get tired after long time working, there will be a high chance of fatigue driving. Many drivers using cigarette for fighting fatigue (at least they believe it is useful) and they will use left hands (window side) to let the smoke vent out. Thus the driver may only use the right hand to control the steering wheel which results in abnormal right lane changes.

VI. DISCUSSION

In this section, we discuss the system latency of proposed models and how these models can be extended with real-time vehicle motion sensing based on IMU sensors for practical implications.



Fig. 12. The recognition accuracy of different time windows.

A. System Latency

In this work, we aim to build robust models which can be implemented into the real-time driving safety systems. For inattentive driving identification, the length of the sampling window (sliding window for data segmentation) plays a very important role in the latency optimization. It also affects whether the driver is able to have enough time to react on road. The size of the sampling window represents the number of GPS points in the given time period. Therefore, as shown in Figure 12, we evaluated different window lengths from 2 points to 7 points. The results show that when the length of the sampling window is set as 6 - it means 6 GPS cells are included (the time period between each pair of GPS points in the record is 2 seconds, thus the time period of a time window is 10 seconds) which achieved the best accuracy. We acknowledge that most of existing driver assistance systems usually employ a 3-second threshold to alert the unsafe event [57]. However, driver inattention is a complex mental process that may occur before there is any actual behavior detected. Our purpose is to infer potential inattentive driving based on the data derived from the vehicle trajectory/dynamics, thus it is not necessary to use 3 seconds as the latency limit but a trade-off between the window length and the detection accuracy is appropriate.

In addition to the analysis of inattentive driving recognition, how far in advance that our model can predict the abnormal operations is also a critical issue worth discussing. In our design, the latency of the prediction model $T_{latency}$ basically depends on the time interval of data (i.e., GPS points) collection T_c (2 seconds).

$$T_{latency} = T_c \times m, \tag{17}$$

where m is the number of time intervals between a detected inattentive event and the abnormal operation that be affected. In this paper, we set m as 1 and then $T_{latency}$ is 2 seconds, or it is 2 seconds prior to the abnormal operation. Though we should predict the unsafe event as earlier as possible, if the time period is over 3 seconds ($T_{latency}$ will be at least 4 seconds when m is beyond 2) there may be another unsafe behavior occurring during such time period.

B. Extended System with IMU Sensors

While our system is able to identify driver inattention and predict abnormal driving based on trajectory data, the models proposed in this work are also capable of processing real-time data obtained from smart/on-board devices (e.g. smartphones) which have GPS and IMU sensors embedded. More specifically, the input data/features for each module (i.e., event spotting, inattentive driving recognition and abnormal operation prediction) have already been extracted from the original GPS trace after preprocessing. For example, the input vector for event spotting consists variables such as average acceleration, average distance, average speed, etc. Then we are using the vehicle velocity offset as the features for inattentive driving recognition and combining the velocity, the heading/moving angle, as well as the geographical (POI and meteorological) information for abnormal operation prediction. All of these input data/features can be obtained directly using GPS and IMU sensors (e.g., accelerometer and gyroscope). Consider that the proposed models do not require a high volume of space on disk (i.e., the size of Inception v3 is only 989 KB - the largest one in the system), we are able to implement our proposed scheme in any off-the-shelf smart devices (i.e., smartphones) with embedded sensors for practical implications. In addition, by taking the advantage of a higher sampling rate (e.g. 20 Hz) of smart sensors, we are able to perform the fine-grained analysis on feature vectors (instead of 2 seconds per GPS point only) thus further improve the system accuracy while at the same time minimize the detection and prediction latency.

VII. CONCLUSION

In this paper, we propose a inattentive driving analytics system that detects driver inattentive behaviors and predicts abnormal driving operations to reduce the risk of traffic accidents. To achieve the goal, we propose a deep Convolutional Neural Network (Inception v3), which can better extract the local features of the trajectory from the set filters of different widths. We use Smote algorithm to increase the sample size to balance the sample and adopt the Mixup module to the trajectory data processing. In the evaluation on large-scale trajectory data, the overall performance of our model is promising. The experiment results shows that the proposed model has great potential to prevent unsafe driving behaviors and thereby encourage us to further our study on aggressive driving style analysis and other types of in-vehicle activity monitoring.

Specifically, as discussed in Section VI-A, the proposed design is capable of processing real-time sensing data (e.g., acceleration and angular speed) obtained from embedded sensors on smart/on-board devices (e.g. smartphones). In the future, a hybrid system combining the smartphone GPS and IMU sensors, as well as wearable devices [6] is desirable for a comprehensive study of driver behaviors, which could provide a practical implementation that not only tracks vehicle dynamics on road, but also monitors driver real-time in-vehicle activities.

VIII. ACKNOWLEDGEMENT

This research was supported in part by NSFC 61872247, Shenzhen Peacock Talent Grant 827-000175, Guangdong Natural Science Fund 2019A1515011064, Lingnan University Direct Grant DR21A6, and Lingnan Research Seed Fund 102363.

REFERENCES

- P. Baranyi, "Distracted driving in fatal crashes 2017," https://crashstats.nhtsa.dot.gov/Api/Public/ViewPublication/812700.
- [2] E. Vural, M. Cetin, A. Ercil, G. Littlewort, M. Bartlett, and J. Movellan, "Drowsy driver detection through facial movement analysis," in *International Workshop on Human-Computer Interaction*. Springer, 2007, pp. 6–18.
- [3] B. Bhowmick and K. C. Kumar, "Detection and classification of eye state in ir camera for driver drowsiness identification," in 2009 IEEE International Conference on Signal and Image Processing Applications. IEEE, 2009, pp. 340–345.
- [4] S. Al-Sultan, A. H. Al-Bayatti, and H. Zedan, "Context-aware driver behavior detection system in intelligent transportation systems," *IEEE Transactions on Vehicular Technology*, vol. 62, no. 9, pp. 4264–4275, 2013.
- [5] C.-W. You, N. D. Lane, F. Chen, R. Wang, Z. Chen, T. J. Bao, M. Montes-de Oca, Y. Cheng, M. Lin, L. Torresani *et al.*, "Carsafe app: Alerting drowsy and distracted drivers using dual cameras on smartphones," pp. 13–26, 2013.
- [6] L. Jiang, X. Lin, X. Liu, C. Bi, and G. Xing, "Safedrive: Detecting distracted driving behaviors using wrist-worn devices," *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, vol. 1, no. 4, pp. 1–22, 2018.
- [7] M. Raja, V. Ghaderi, and S. Sigg, "Wibot! in-vehicle behaviour and gesture recognition using wireless network edge," 2018 IEEE 38th International Conference on Distributed Computing Systems, pp. 376– 387, 2018.
- [8] F. Wang, J. Liu, and W. Gong, "Wicar: Wifi-based in-car activity recognition with multi-adversarial domain adaptation," 2019 IEEE/ACM 27th International Symposium on Quality of Service, pp. 1–10, 2019.
- [9] X. Xu, H. Gao, J. Yu, Y. Chen, Y. Zhu, G. Xue, and M. Li, "Er: Early recognition of inattentive driving leveraging audio devices on smartphones," *IEEE Conference on Computer Communications*, pp. 1–9, 2017.
- [10] W. Jia, H. Peng, N. Ruan, Z. Tang, and W. Zhao, "Wifind: Driver fatigue detection with fine-grained wi-fi signal features," *IEEE Transactions on Big Data*, vol. 6, pp. 269–282, 2020.
- [11] SMARTwheel, "The first intelligent steering wheel cover." https://smartwheelusa.com/.
- [12] Y. Dong, Z. Hu, K. Uchimura, and N. Murayama, "Driver inattention monitoring system for intelligent vehicles: A review," *IEEE Transactions* on *Intelligent Transportation Systems*, vol. 12, no. 2, pp. 596–614, 2010.
- [13] B. Jacob and E. Violette, "Vehicle trajectory analysis: an advanced tool for road safety," *Procedia-Social and Behavioral Sciences*, vol. 48, pp. 1805–1814, 2012.
- [14] C. Chen, D. Zhang, Y. Wang, and H. Huang, *Enabling Smart Urban Services with GPS Trajectory Data*. Springer Nature, 2021.
- [15] J. Paefgen, F. Kehr, Y. Zhai, and F. Michahelles, "Driving behavior analysis with smartphones: insights from a controlled field study," in *Proceedings of the 11th International Conference on mobile and ubiquitous multimedia*, 2012, pp. 1–8.
- [16] L. Jiang, X. Chen, and W. He, "Safecam: Analyzing intersectionrelated driver behaviors using multi-sensor smartphones," in 2016 IEEE International Conference on Pervasive Computing and Communications (PerCom). IEEE, 2016, pp. 1–9.
- [17] M. Fazeen, B. Gozick, R. Dantu, M. Bhukhiya, and M. C. González, "Safe driving using mobile phones," *IEEE Transactions on Intelligent Transportation Systems*, vol. 13, no. 3, pp. 1462–1468, 2012.
- [18] K. B. Ahmed, B. Goel, P. Bharti, S. Chellappan, and M. Bouhorma, "Leveraging smartphone sensors to detect distracted driving activities," *IEEE Transactions on Intelligent Transportation Systems*, vol. 20, no. 9, pp. 3303–3312, 2018.
- [19] Y. Wang, Y. J. Chen, J. Yang, M. Gruteser, R. P. Martin, H. Liu, L. Liu, and C. Karatas, "Determining driver phone use by exploiting smartphone integrated sensors," *IEEE Transactions on Mobile Computing*, vol. 15, no. 8, pp. 1965–1981, 2015.

- [20] P. Subirats, Y. Goyat, B. Jacob, and E. Violette, "A new road safety indicator based on vehicle trajectory analysis," *Transportation research procedia*, vol. 14, pp. 4267–4276, 2016.
- [21] Honda, "Driver attention monitor," https://www.hondainfocenter.com/2021/CR-V/Feature-Guide/Interior-Features/Driver-Attention-Monitor/.
- [22] P. Choudhary and N. R. Velaga, "Analysis of vehicle-based lateral performance measures during distracted driving due to phone use," *Transportation Research Part F: Traffic Psychology and Behaviour*, vol. 44, pp. 120–133, 2017.
- [23] Q. Ji, Z. Zhu, and P. Lan, "Real-time nonintrusive monitoring and prediction of driver fatigue," *IEEE Transactions on Vehicular Technology*, vol. 53, no. 4, pp. 1052–1068, 2004.
- [24] L. Xu, S. Li, K. Bian, T. Zhao, and W. Yan, "Sober-drive: A smartphoneassisted drowsy driving detection system," in 2014 International Conference on Computing, Networking and Communications. IEEE, 2014, pp. 398–402.
- [25] M.-C. Chuang, R. Bala, E. A. Bernal, P. Paul, and A. Burry, "Estimating gaze direction of vehicle drivers using a smartphone camera," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, 2014, pp. 165–170.
- [26] A. Ghosh, T. Chatterjee, S. Samanta, J. Aich, and S. Roy, "Distracted driving: A novel approach towards accident prevention," *Adv. Comput. Sci. Technol*, vol. 10, pp. 2693–2705, 2017.
- [27] D. Lee, S. Oh, S. Heo, and M. Hahn, "Drowsy driving detection based on the driver's head movement using infrared sensors," in 2008 Second International Symposium on Universal Communication. IEEE, 2008, pp. 231–236.
- [28] R. Torres, O. Ohashi, E. Carvalho, and G. Pessin, "A deep learning approach to detect distracted drivers using a mobile phone," in *International Conference on Artificial Neural Networks*. Springer, 2017, pp. 72–79.
- [29] A. A. Assefa and T. Wenhong, "Bio-mechanical distracted driver recognition based on stacked autoencoder and convolutional neural network," in 2019 IEEE 2nd International Conference on Information Communication and Signal Processing. IEEE, 2019, pp. 449–453.
- [30] C. Streiffer, R. Raghavendra, T. Benson, and M. Srivatsa, "Darnet: a deep learning solution for distracted driving detection," in *Proceedings* of the 18th Acm/Ifip/Usenix Middleware Conference: Industrial Track, 2017, pp. 22–28.
- [31] Y. Xing, C. Lv, H. Wang, D. Cao, E. Velenis, and F.-Y. Wang, "Driver activity recognition for intelligent vehicles: A deep learning approach," *IEEE Transactions on Vehicular Technology*, vol. 68, no. 6, pp. 5379– 5390, 2019.
- [32] Y. Xie, F. Li, Y. Wu, S. Yang, and Y. Wang, "D3-guard: Acoustic-based drowsy driving detection using smartphones," in 2019-IEEE Conference on Computer Communications. IEEE, 2019, pp. 1225–1233.
- [33] J. Yang, S. Sidhom, G. Chandrasekaran, T. Vu, H. Liu, N. Cecan, Y. Chen, M. Gruteser, and R. P. Martin, "Detecting driver phone use leveraging car speakers," pp. 97–108, 2011.
- [34] B. Goel, A. K. Dey, P. Bharti, K. B. Ahmed, and S. Chellappan, "Detecting distracted driving using a wrist-worn wearable," in 2018 IEEE International Conference on Pervasive Computing and Communications Workshops. IEEE, 2018, pp. 233–238.
- [35] C. Bi, J. Huang, G. Xing, L. Jiang, X. Liu, and M. Chen, "Safewatch: a wearable hand motion tracking system for improving driving safety," *ACM Transactions on Cyber-Physical Systems*, vol. 4, no. 1, pp. 1–21, 2019.
- [36] B.-L. Lee, B.-G. Lee, and W.-Y. Chung, "Standalone wearable driver drowsiness detection system in a smartwatch," *IEEE Sensors journal*, vol. 16, no. 13, pp. 5444–5451, 2016.
- [37] Y. Wang, J. Yang, H. Liu, Y. Chen, M. Gruteser, and R. P. Martin, "Sensing vehicle dynamics for determining driver phone use," in *International Conference on Mobile Systems, Applications, and Services*, 2013, pp. 41–54.
- [38] G. Johnson and R. Rajamani, "Smartphone localization inside a moving car for prevention of distracted driving," *Vehicle system dynamics*, vol. 58, no. 2, pp. 290–306, 2020.
- [39] Z. Chen, J. Yu, Y. Zhu, Y. Chen, and M. Li, "D3: Abnormal driving behaviors detection and identification using smartphone sensors," in *IEEE International Conference on Sensing, Communication, and Networking*. IEEE, 2015, pp. 524–532.
- [40] A. Bhaskar, "Eyeawake: A cost effective drowsy driver alert and vehicle correction system," in 2017 International Conference on Innovations in Information, Embedded and Communication Systems (ICHECS). IEEE, 2017, pp. 1–6.

- [41] M. L. Watkins, I. A. Amaya, P. E. Keller, M. A. Hughes, and E. D. Beck, "Autonomous detection of distracted driving by cell phone," in 2011 14th International IEEE Conference on Intelligent Transportation Systems (ITSC). IEEE, 2011, pp. 1960–1965.
- [42] U. S. D. o. T. NHTSA, "Distracted driving," https://www.nhtsa.gov/risky-driving/distracted-driving.
- [43] R. L. Olson, R. J. Hanowski, J. S. Hickman, J. Bocanegra *et al.*, "Driver distraction in commercial vehicle operations," United States. Department of Transportation. Federal Motor Carrier Safety ..., Tech. Rep., 2009.
- [44] P. Schroeder, M. Wilbur, R. Peña *et al.*, "National survey on distracted driving attitudes and behaviors-2015," United States. National Highway Traffic Safety Administration, Tech. Rep., 2018.
- [45] H. Han, W. Wang, and B. Mao, "Borderline-smote: A new over-sampling method in imbalanced data sets learning," in *International Conference* on Intelligent Computing, 2005.
- [46] A. Liaw and M. Wiener, "Classification and regression by randomforest," *R News*, vol. 23, no. 23, 2002.
- [47] C. Szegedy, W. Liu, Y. Jia, P. Sermanet, S. Reed, D. Anguelov, D. Erhan, V. Vanhoucke, and A. Rabinovich, "Going deeper with convolutions," in *IEEE Conference on Computer Vision and Pattern Recognition*, 2015, pp. 1–9.
- [48] H. Zhang, M. Cisse, Y. N. Dauphin, and D. Lopez-Paz, "mixup: Beyond empirical risk minimization," arXiv preprint arXiv:1710.09412, 2017.
- [49] C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna, "Rethinking the inception architecture for computer vision," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016, pp. 2818–2826.
- [50] J. Bjorck, C. Gomes, B. Selman, and K. Q. Weinberger, "Understanding batch normalization," 2018.
- [51] G. Lugosi and K. Zeger, "Nonparametric estimation via empirical risk minimization," *IEEE Transactions on information theory*, vol. 41, no. 3, pp. 677–687, 1995.
- [52] J. H. Friedman, "Greedy function approximation: a gradient boosting machine," Annals of statistics, pp. 1189–1232, 2001.
- [53] V. VN, "Statistical learning theory," Encyclopedia of the Sciences of Learning, vol. 41, no. 4, pp. 3185–3185, 1998.
- [54] J. M. Keller, M. R. Gray, and J. A. Givens, "A fuzzy k-nearest neighbor algorithm," *IEEE Transactions on Systems Man Cybernetics*, vol. SMC-15, no. 4, 2012.
- [55] J. Cohen, Applied multiple regression/correlation analysis for the behavioral sciences. L. Erlbaum Associates,, 2003.
- [56] A. Graves, A. R. Mohamed, and G. Hinton, "Speech recognition with deep recurrent neural networks," in *IEEE International Conference on Acoustics*, 2013.
- [57] NHTSA, "Breakthrough research on real-world driver behavior released." https://www.nhtsa.gov/DrivingSafety/.



Dian Zhang received her Ph.D. degree in computer science and engineering from the Hong Kong University of Science and Technology (HKUST), Hong Kong, in 2010. After that, she worked as a research assistant professor at the Fok Ying Tung Graduate School, HKUST. She also worked as associate professor at Lingnan University before. She is currently an associate professor at Shenzhen University. Her research interests include big data analytics and mobile computing.



Tao Gu is currently a Professor in Department of Computing at Macquarie University, Australia. His research interests include Internet of Things, ubiquitous computing, mobile computing, embedded AI, wireless sensor networks, and big data analytics. He is currently serving as an Editor of IMWUT, an Associate Editor of TMC and IoT-J. Please find out more information at https://taogu.site.



Landu Jiang received his Ph.D. in computer science from McGill University, in 2018. He received his master's degree in computer science and minor in construction management at University of Nebraska-Lincoln, in 2012. Previously, He received his BEng in information security engineering from Shanghai Jiao Tong University, in 2010. His research interests include ubiquitous computing, machine learning applications, mobile computing, computer vision, cyber-physical systems, and green energy solutions.



Wen Xie received his master's degree in the College of Computer Science and Software Engineering at Shenzhen University, in 2021. He received his BEng in computer science and engineering from Guangzhou college of South China University of Technology, in 2018. His research interests include machine learning, neural networks and internet of things.